



VETERAN SAFETY SUPPLY LLC
A Service Disabled Veteran Owned Small Business



DOUBLE-COATED TAPE

DOUBLE-SIDED PRESSURE-SENSITIVE SUPER-HOLD

Our Double Coated Tape is clear polyester, and features a 1/2 mil thick polyester film coated on both sides with an extremely aggressive acrylic adhesive system.

This splicing tape is used in the manufacturing of paper, plastics, and other continuous web processes. It is especially suitable in the manufacture of corrugated paper. Adheres well to both kraft and coated paper.

An excellent mounting and laminating system for use with dissimilar metals, foams, foils, and name plates. Thickness conformability is excellent for most irregular and mismatched surfaces.

SIZE	THICKNESS	TEMPERATURE RANGE	ROLLS / CTN	CTN DIMENSIONS (L x W x H)	SHIPPING WEIGHT	CTNS / PALLET
1/2" x 60 YD	2 mil	-17F to 300F	96	12.0" x 12.0" x 12.0"	29 LBS	36
1.0" x 60 YD	2 mil	-17F to 300F	48	11.0" x 11.0" x 13.0"	30 LBS	36
2.0" x 55 YD	2 mil	-17F to 300F	24	12.0" x 12.0" x 13.0"	25 LBS	36
3.0" x 60 YD	2 mil	-17F to 300F	16	12.0" x 12.0" x 12.0"	31 LBS	36

IF YOU DON'T SEE WHAT YOU NEED, PLEASE ASK!
ORDERS & INQUIRIES: (412) 376-8937